



Super Elastics

SC20 Energy+

Energy saver



The SC20 Energy+ is ideally suited to electric vehicles. Its optimized compound provides very low energy consumption and with it, low operating costs- without reduction in traction and stability.

Product features

Low energy consumption
Outstanding stability
Excellent traction
Low rolling resistance

SH12 /Trailer

Particularly robust



With its slick tread and the closed shoulders, the SH12 is an excellent solution when low energy consumption, high driving comfort through smooth running and protection against damages are required.

Product features

High mileage performance
Low vibrations
Excellent driving comfort
High traction
Low rolling resistance

SC11

High cornering



The SC11 offers high driving stability due to the scope-oriented tread. Moreover, the flat, closed tread offers good steering response and has excellent cornering stability.

Product features

High mileage performance
Low vibrations
Excellent driving comfort
High driving stability
Excellent cornering stability

CSE-Robust

Proven all-rounder



The tire for use on small tractors and trailers. The CSE-Robust design offers optimal protection against cuts and punctures.

The tire is available in size 3.00-4.

Product features

Good traction
Good cornering stability
High security for small tractor units and trailers



Press on Bands

MH20

Compact and strong



The Continental MH20 is the heavy duty king. Its sturdy construction allows the MH20 to have high lifting capacities simultaneously with small wheel sizes. It is therefore excellent for vehicles that need to transport heavy items with low ceiling heights.

Product features

- Large load capacity
- High mileage performance
- Sturdy design
- High tilting stability
- Less rolling resistance

MC20

Traction & high load capacity



If low passage heights, heavy loads and maintaining high levels of traction are required, the Continental MC20 proves its strengths. Despite its compact design, the MC20 has a profile with a smooth tread. Therefore heavy loads can be transported safely on almost all surfaces.

Product features

- High tilting stability
- Large load capacity
- Less rolling resistance
- Sturdy design
- Good traction

ContiPT18

The all-rounder



The ContiPT18 transports the superior driving forces of a super elastic tire onto a Press on Bands. With its special tread it achieves excellent levels of traction, combined with high loads.

Product features

- High tilting stability
- Large load capacity
- Less rolling resistance
- Sturdy design
- High traction
- Good cornering stability

Versions

Clean (Non-marking)



For clean use.

Clean tires are used in particularly dust and dirt-sensitive areas. Visually, they are quick to recognize by their bright coloured rubber. Their special feature is that the tire tracks on the ground, and hence soiling in production and storage areas, are reduced.

The following products are available in Clean version:

Super Elastic tires

SC20

CS20

CSEasy

SH12

SC11

CSERobust

Press on Bands

MH20

MC20

ContiPT18

Typical application areas

- › Automotive industry
- › Food & Beverage
- › Computers & Electronics
- › Paper
- › Solar industry
- › Optical & opto-electronic industry
- › Chemical and pharmaceutical
- › Aviation & Aerospace

Dimensions

Super Elastics

Dimension		Wheel type	SC20 Energy+	SC20 Mileage+	CS20	LifeCycle	CS Easy SC20
8"							
125/75 - 8/3.00	15X4 1/2-8	S	●	○	○	○	○
		SIT	●	○	●	●	●
150/75 - 8/4.33	16X6-8	S	●	●	○	○	○
		SIT	●	●	●	●	●
180/70 - 8/4.33	18X7-8	S	●	●	○	○	○
		SIT	●	●	●	●	●
4.00 - 8/3.00		S	●	○	○	○	○
		SIT	●	○	●	○	○
5.00 - 8/3.00		S	●	●	○	●	○
		SIT	●	●	○	●	●
9"							
140/55 - 9/4.00		S	●	○	○	○	○
		SIT	●	●	●	●	○
200/75 - 9/6.00	21X8-9	S	●	●	○	○	○
		SIT	●	●	○	●	●
6.00 - 9/4.00		S	●	●	○	●	○
		SIT	●	●	●	●	●
10"							
180/60 - 10/5.00		S	●	○	○	○	○
		SIT	●	○	●	○	●
200/50 - 10/6.50		S	●	○	○	○	○
		SIT	●	●	●	●	●
225/75 - 10/6.50	23X9-10	S	●	●	○	○	○
		SIT	●	●	●	●	●
6.50 - 10/5.00		S	○	●	○	●	○
		SIT	○	●	●	●	●
12"							
250/60 - 12/8.00	23X10-12	S	●	○	○	○	○
		SIT	●	●	●	●	●
250/75 - 12/8.00	27X10-12	S	○	●	○	○	○
		SIT	●	●	●	●	●
315/45 - 12/10.00		SIT	●	●	●	○	○
		S	●	●	○	●	○
7.00 - 12/5.00		S	●	●	○	●	○
		SIT	●	●	●	●	●
13"							
23 X 5/3.75		S	●	○	○	○	○
		SIT	●	○	○	○	○

Dimension		Wheel type	SC20 Energy+	SC20 Mileage+	CS20	LifeCycle	CS Easy SC20
15"							
225/75 - 15/7.00	28X9-15	S	○	●	○	○	○
		SIT	●	●	●	●	○
250/70 - 15/7.00		S	●	●	○	○	○
		SIT	●	●	●	●	○
315/70 - 15/8.00		S	○	●	○	○	○
		SIT	●	●	●	●	○
355/45 - 15/9.75	28X12 1/2-15	S	●	○	○	○	○
		SIT	●	○	●	○	○
355/50 - 15/9.75		SIT	●	○	○	○	○
355/65 - 15/9.75		S	○	●	○	○	○
		SIT	●	●	●	●	○
7.00 - 15/5.50		S	●	●	○	○	○
		SIT	●	●	●	○	○
7.50 - 15/6.50		S	○	●	○	○	○
		SIT	○	●	○	○	○
8.25 - 15/6.50		S	○	●	○	●	○
		SIT	●	●	●	●	○
20"							
8.25 - 20/6.50		S	○	●	○	○	○
		SIT	○	●	○	○	○
10.00 - 20/7.50		S	○	●	○	○	○
10.00 - 20/8.00		S	○	●	○	○	○
		SIT	○	●	○	○	○
12.00 - 20/8.00		S	○	●	○	○	○
12.00 - 20/8.50		S	○	●	○	○	○
		SIT	○	●	○	○	○
12.00 - 20/10.00		S	○	●	○	○	○
355/50 - 20/10.00		SIT	○	●	○	○	○
24"							
12.00 - 24/8.50		S	○	●	○	○	○
12.00 - 24/10.00		S	○	●	○	○	○
14.00 - 24/10.00		S	○	●	○	○	○

- Available
- Unavailable

Various dimensions are also available in clean and conductive versions.
Your sales representative will be glad to advise you.

Dimension		Wheel type	SH12/Trailer	SC11	CSE-Robust	SC10	SC15
4"							
3.00 - 4		M	○	○	●	○	○
4.00 - 4		M	○	○	○	●	○
6"							
140/55-6 /4.50		M/S	○	○	○	○	●
8"							
4.00 - 8/3.00		S	○	○	○	○	●
		SIT	○	○	○	○	●
5.00 - 8/3.00		S	○	○	○	○	●
		SIT	○	○	○	○	●
125/75 - 8/3.00	15X4 1/2-8	S	●	○	○	○	●
		SIT	●	○	○	○	●
15 X 4 1/2 - 8		S	○	●	○	○	●
		SIT	○	○	○	○	●
150/75 - 8/4.33	16X6-8	S	●	○	○	○	●
		SIT	●	○	○	○	●
180/70 - 8/4.33		S	●	○	○	○	●
		SIT	●	○	○	○	●
9"							
140/55 - 9/4.00		SIT	○	●	○	○	○
200/75 - 9/6.00	21X8-9	S	○	○	○	○	●
		SIT	○	○	○	○	●
6.00 - 9/4.00		S	○	●	○	○	●
		SIT	○	●	○	○	●
10"							
180/60 - 10/5.00		S	○	○	○	○	●
		SIT	●	○	○	○	●
200/50 - 10/6.50		S	○	○	○	○	●
		SIT	●	○	○	●	●
225/75 - 10/6.50	23X9-10	S	●	○	○	○	●
		SIT	●	○	○	○	●
6.50 - 10/5.00		S	○	○	○	○	●
		SIT	○	○	○	○	●
12"							
250/75 - 12/8.00	27X10-12	S	○	○	○	○	●
		SIT	○	○	○	○	●
7.00 - 12/5.00		S	○	○	○	○	●
		SIT	○	○	○	○	●
13"							
6.00 - 13		SIT	○	●	○	○	○
160/90 - 13/3.75		SIT	○	●	○	○	○
160/95 - 13		SIT	○	●	○	○	○
22 X 4 1/2		SIT	○	○	○	●	○

Dimension		Wheel type	SH12/Trailer	SC11	CSE-Robust	SC10	SC15
25 X 6							
		S	○	○	○	●	○
		SIT	○	○	○	●	○
15"							
225/75 - 15/7.00	28X9-15	S	○	○	○	○	●
		SIT	○	○	○	○	●
250/70 - 15/7.00		S	○	○	○	○	●
		SIT	●	○	○	○	●
250/70 - 15/7.50		S	●	○	○	○	●
		SIT	●	○	○	○	●
315/70 - 15/8.00		S	○	○	○	○	●
		SIT	○	○	○	○	●
355/45 - 15/9.75	28X12 1/2-15	S	○	○	○	○	●
		SIT	○	○	○	○	●
355/65 - 15/9.75		S	○	○	○	○	●
		SIT	○	○	○	○	●
7.00 - 15/5.50		S	○	○	○	○	●
		SIT	○	○	○	○	●
7.50 - 15/6.50		S	○	○	○	○	●
		SIT	○	○	○	○	●
8.25 - 15/6.50		S	●	○	○	○	●
		SIT	●	○	○	○	●
20"							
8.25 - 20/6.50		S	○	○	○	○	●
		SIT	○	○	○	○	●
10.00 - 20/6.50		S	○	○	○	○	●
		SIT	○	○	○	○	●
10.00 - 20/7.50		S	●	○	○	○	○
10.00 - 20/8.00		S	●	○	○	○	●
		SIT	○	○	○	○	●
12.00 - 20/8.00		S	○	○	○	○	●
355/50 - 20/10.00		S	●	○	○	○	●
		SIT	●	○	○	○	●
24"							
10.00 - 20/7.50		S	○	○	○	○	●
12.00 - 20/8.50		S	○	○	○	○	●
12.00 - 20/10.00		S	○	○	○	○	●
12.00 - 24/8.50		S	○	○	○	○	●
12.00 - 24/10.00		S	○	○	○	○	●
		SIT	○	○	○	○	●
14.00 - 24/10.00		S	○	○	○	○	●
		SIT	○	○	○	○	●

Dimensions

Press on Bands

Dimension	Wheel type	MH20	MC20	ContiPT18
65mm				
105/45 - 65	Z	●	○	○
75mm				
125/50 - 75	KM15	●	○	○
	Z	●	○	○
100mm				
150/50 - 100	KM15	●	○	○
	Z	●	○	○
160/50 - 100	KM15	●	○	○
	Z	●	○	○
170/75 - 100	Z	●	●	○
200/75 - 100	KM15	●	○	○
	Z	●	○	○
105mm				
200/85 - 105	KM15	●	○	○
	Z	●	○	○
120mm				
180/50 - 120	KM15	●	○	○
	STB	●	○	○
	Z	●	○	○
230/75 - 120	Z	●	○	○
140mm				
200/50 - 140	KM15	●	○	○
	STB	●	○	○
	Z	●	○	○
250/75 - 140	KM15	●	○	○
	STB	●	○	○
	Z	●	○	○
250/100 - 140	Z	●	○	○
250/130 - 140	STB	●	○	○
	Z	●	○	○
150mm				
200/60 - 150	Z	●	○	○
160mm				
265/160 - 160	STB	●	○	○
	Z	●	○	○
165mm				
254/102 - 165	10X4X6 1/2	STB	●	○
254/127 - 165	10X5X6 1/2	STB	●	○
267/127 - 165	10 1/2X5X6 1/2	STB	●	○
170mm				
230/50 - 170	KM15	●	○	○
	STB	●	○	○
	Z	●	○	○
230/75 - 170	STB	●	○	○
250/105 - 170	STB	●	○	○
250/60 - 170	KM15	●	○	○
	Z	●	○	○

Dimension	Wheel type	MH20	MC20	ContiPT18
250/75 - 170	Z	●	○	○
250/80 - 170	STB	●	○	○
	Z	●	○	○
260/60 - 170	KM15	●	○	○
	Z	●	○	○
270/105 - 170	Z	●	○	○
280/75 - 170	KM15	●	○	○
	Z	●	○	○
300/85 - 170	Z	●	○	○
310/100 - 170	Z	●	○	○
190mm				
250/50 - 190	KM15	●	○	○
	Z	●	○	○
250/60 - 190	STB	●	○	○
	Z	●	○	○
250/85 - 190	STB	●	○	○
280/60 - 190	STB	●	○	○
	Z	●	○	○
200mm				
310/75 - 200	KM15	●	○	○
310/120 - 200	KS15/6	●	○	○
310/140 - 200	KS15/6	●	○	○
203mm				
300/90 - 203	Z	●	○	○
300/100 - 203	KM8	●	○	○
	STB	●	○	○
	Z	●	○	○
305/114 - 203	12X4 1/2X8	STB	●	○
330/114 - 203	13X4 1/2X8	STB	●	○
330/127 - 203	13X5X8	STB	○	●
343/140 - 203	13 1/2X5 1/2X8	KS15/6	●	○
	STB	●	●	○
356/114 - 203	14X4 1/2X8	STB	●	●
220mm				
280/50 - 220	STB	●	○	○
	Z	●	○	○
280/75 - 220	KM10	●	○	○
	Z	●	○	○
285/75 - 220	STB	●	○	○
300/50 - 220	KM15	●	○	○
	KM10	●	○	○
	Z	●	○	○
310/60 - 220	Z	●	○	○
310/120 - 220	Z	●	○	○
254mm				
356/127 - 254	14X5X10	STB	●	○
394/152 - 254	15 1/2X6X10	STB	○	○
267mm				
406/127 - 267	16X5X10 1/2	KS15/6	●	○
	STB	●	●	●
406/152 - 267	16X6X10 1/2	KS15/6	●	○
	STB	●	●	●
406/178 - 267	16X7X10 1/2	KS15/6	●	○
	STB	●	○	○

Dimension		Wheel type	MH20	MC20	ContiPT18
270mm					
360/60 - 270		KM15	●	○	○
		STB	●	○	○
		Z	●	○	○
360/75 - 270		KM15	●	○	○
		Z	●	○	○
360/85 - 270		KM15	●	○	○
		STB	●	○	○
		Z	●	○	○
286mm					
381/127 - 286	15X5X11 1/4	STB	●	●	○
413/127 - 286	16 1/4X5X11 1/4	STB	●	●	○
413/152 - 286	16 1/4X6X11 1/4	STB	●	●	●
413/178 - 286	16 1/4X7X11 1/4	STB	●	●	○
300mm					
450/120 - 300		STB	●	○	○
305mm					
400/65 - 305		Z	●	○	○
400/75 - 305		KM15	●	○	○
		Z	●	○	○
405/65 - 305		STB	●	○	○
405/130 - 305		STB	●	○	○
		Z	●	○	○
405/260 - 305		STB	●	○	○
415/75 - 305		STB	●	○	○
415/90 - 305		STB	●	○	○
		Z	●	○	○
415/100 - 305		KM8	●	○	○
		STB	●	○	○
		Z	●	○	○
425/150 - 305		STB	●	○	○
		Z	●	○	○
425/260 - 305		STB	●	○	○
425/300 - 305		STB	●	○	○
450/300 - 305		STB	●	○	○
455/100 - 305		Z	●	○	○
308mm					
457/127 - 308	18X5X12 1/8	STB	●	●	○
457/152 - 308	18X6X12 1/8	STB	●	●	●
457/178 - 308	18X7X12 1/8	KS15/6	●	○	○
		STB	●	●	●
457/203 - 308	18X8X12 1/8	STB	●	●	●
457/229 - 308	18X9X12 1/8	STB	○	●	○
330mm					
533/229 - 330	21X9X13	KS15/8	●	○	○
370mm					
500/85 - 370		Z	●	○	○
520/100 - 370		STB	●	○	○
		Z	●	○	○
525/100 - 370		Z	●	○	○

Dimension		Wheel type	MH20	MC20	ContiPT18
381mm					
533/127 - 381	21X5X15	STB	●	○	○
533/152 - 381	21X6X15	STB	○	●	○
533/178 - 381	21X7X15	STB	●	●	●
533/203 - 381	21X8X15	STB	●	●	●
533/229 - 381	21X9X15	STB	●	○	●
406mm					
559/152 - 406	22X6X16	STB	●	○	○
559/203 - 406	22X8X16	STB	●	●	●
559/229 - 406	22X9X16	STB	●	●	●
559/254 - 406	22X10X16	STB	●	●	○
559/305 - 406	22X12X16	STB	●	●	●
559/356 - 406	22X14X16	STB	●	○	○
559/406 - 406	22X16X16	STB	●	○	○
410mm					
500/65 - 410		STB	●	○	○
		Z	●	○	○
540/200 - 410		Z	●	○	○
550/120 - 410		KM8	●	○	○
		Z	●	○	○
550/160 - 410		STB	●	○	○
		Z	●	○	○
560/100 - 410		STB	●	○	○
		Z	●	○	○
590/120 - 410		Z	●	○	○
610/150 - 410		STB	●	○	○
		Z	●	○	○
620/200 - 410		STB	●	○	○
		Z	●	○	○
645/250 - 410		STB	●	○	○
		Z	●	○	○
645/300 - 410		STB	●	○	○
480mm					
620/420 - 480		STB	●	○	○
645/200 - 480		KS15/8	○	●	○
		STB	●	○	○
645/250 - 480		STB	●	○	○
500mm					
760/250 - 500		STB	●	○	○
559mm					
711/254 - 559	28X10X22	STB	●	○	○
711/305 - 559	28X12X22	STB	●	●	○
711/356 - 559	28X14X22	STB	●	○	○
840/356 - 559		STB	●	○	○
840/406 - 559		STB	●	○	○
840/500 - 559		STB	●	○	○
640mm					
750/75 - 640		Z	●	○	○
670mm					
920/250 - 670		STB	●	○	○
920/400 - 670		STB	●	○	○
762mm					
1016/406 - 762	40X16X30	STB	●	○	○